



hetech block

MONOLITH					
	Footprint (l x w)*	Required room height	Weight	Net block size after cutting	Net throughput EPS 100 – EN13163
ME3-10	11500 x 6250 mm	5200 mm	14000 kg	3000 x 1200 x 1000 mm	75 m³/h
ME4-10	11500 x 6250 mm	6300 mm	16000 kg	4000 x 1200 x 1000 mm	100 m³/h
ME5-10	11500 x 6250 mm	7300 mm	19000 kg	5000 x 1200 x 1000 mm	120 m³/h
ME6-10	11500 x 6250 mm	8300 mm	23000 kg	6000 x 1200 x 1000 mm	142 m³/h
MA16-4	41' x 21'	40000 lb	40000 lb	16' x 4' x 4'	5100 ft³/h
MA18-4	41' x 21'	46300 lb	46300 lb	18' x 4' x 4'	5600 ft³/h
MA20-4	41' x 21'	51000 lb	51000 lb	20' x 4' x 4'	6100 ft³/h
MA24-4	41' x 21'	57600 lb	57600 lb	24' x 4' x 4'	7000 ft³/h

Above specified dimension are only indicative.
* includes blockmold, exit line, pre-filling silo, vacuum unit and condenser

MONOLITH COMP					
	Footprint (l x w)*	Required room height	Weight	Net block size after cutting	Net throughput EPS 100 – EN13163
MCE24-12	13000 x 7200 mm	5000 mm	15000 kg	2400 x 1400 / 800 x 1200 mm	80 m³/h
MCE3-10	12500 x 7200 mm	5500 mm	21000 kg	3000 x 1400 / 800 x 1000 mm	84 m³/h
MCE4-10	12500 x 7200 mm	6300 mm	24000 kg	4000 x 1400 / 800 x 1000 mm	112 m³/h
MCE4-10XL	12500 x 7500 mm	6300 mm	25000 kg	4000 x 1600 / 1000 x 1000 mm	128 m³/h
MCE4-12XL	13000 x 7500 mm	6300 mm	27000 kg	4000 x 1600 / 1000 x 1200 mm	154 m³/h
MCE48-12	13000 x 7200 mm	7200 mm	28000 kg	4800 x 1400 / 800 x 1200 mm	159 m³/h
MCE5-10	13000 x 7200 mm	7300 mm	26000 kg	5000 x 1400 / 800 x 1000 mm	138 m³/h
MCE5-12	13000 x 7200 mm	7300 mm	27500 kg	5000 x 1400 / 800 x 1200 mm	165 m³/h
MCE6-10	12500 x 7200 mm	8300 mm	28000 kg	6000 x 1400 / 800 x 1000 mm	160 m³/h
MCA16-4	43' x 24'	23'	57000 lb	16' x 56" / 32" x 4'	5850 ft³/h
MCA18-4	43' x 24'	26'	62000 lb	18' x 56" / 32" x 4'	6400 ft³/h
MCA20-4	43' x 24'	27'	64000 lb	20' x 56" / 32" x 4'	7000 ft³/h
MCA24-4	43' x 24'	32'	70000 lb	24' x 56" / 32" x 4'	8100 ft³/h

Above specified dimension are only indicative.
 * includes blockmold, exit line, pre-filling silo, vacuum unit and condenser

OYSTER COMP					
	Footprint (l x w)*	Required room height	Weight	Net block size after cutting	Net throughput EPS 100 – EN13163
OCE4-10	14000 x 7000 mm	6000 mm	24000 kg	4000 x 1400 / 800 x 1000 mm	112 m³/h
OCE4-10XL	14000 x 8000 mm	6000 mm	25000 kg	4000 x 1600 / 1000 x 1000 mm	128 m³/h
OCE4-12XL	14000 x 8000 mm	6000 mm	30000 kg	4000 x 1600 / 1000 x 1200 mm	154 m³/h
OCE48-12	14000 x 7000 mm	6000 mm	35000 kg	4800 x 1400 / 1200 x 1200 mm	161 m³/h
OCE5-10	14000 x 7000 mm	6000 mm	35000 kg	5000 x 1400 / 800 x 1000 mm	140 m³/h
OCE5-12	14000 x 7000 mm	6000 mm	37000 kg	5000 x 1400 / 800 x 1200 mm	168 m³/h
OCE6-10	14000 x 7000 mm	6000 mm	39000 kg	6000 x 1400 / 800 x 1000 mm	168 m³/h
OCE8-10	14000 x 7000 mm	6000 mm	45000 kg	8000 x 1400 / 800 x 1000 mm	225 m³/h
OCA16-4	53' x 23'	16'	77000 lb	16' x 56" / 32" x 4'	5850 ft³/h
OCA18-4	55' x 23'	16'	81000 lb	18' x 56" / 32" x 4'	6600 ft³/h
OCA20-4	56' x 23'	16'	88000 lb	20' x 56" / 32" x 4'	7350 ft³/h
OCA24-4	69' x 23'	16'	92000 lb	24' x 56" / 32" x 4'	8800 ft³/h

OYSTER OSC2					
OSCE6-4-10	20000 x 8000 mm	6000 mm	40000 kg	6000 / 4000 x 1400 / 1000 x 1000 mm	168 m³/h
OSCE8-6-10	25000 x 8000 mm	6000 mm	46000 kg	8000 / 6000 x 1400 / 1000 x 1000 mm	225 m³/h
OSCA18-14-4	66' x 26'	19,7'	88200 lb	18 / 14' x 56 / 40" x 4'	6600 ft³/h
OSCA24-20-4	79' x 26'	19,7'	99000 lb	24 / 20' x 56 / 40" x 4'	8800 ft³/h

OPTIONS BLOCKMOLD

- Weighing scale
- Marking unit & stand
- Density control system
- Water management
- Mixing / de-dusting unit 2 - 4 bags
- Fully automated emptying system
- Emission collection system
- Active Dedusting
- Additional pre-filling silo
- Labelling unit & stand
- High density kit
- Central greasing device
- Air cooler venitlators
- Cooling tower
- Dust collection system

Above specified dimension are only indicative.
 * includes blockmold, exit line, pre-filling silo, vacuum unit and condenser